

# Hi-Q Components

Hi-Q Electronics Ltd, PO Box 302 015, North Harbour, Auckland, New Zealand Ph + 64 9 415 3333 Fax + 64 9 415 8686

## FSF Quick Acting Low Breaking Capacity (Std Fuse)

A quality fusible link for most applications. IEC127 Standard.


Breaking Capacity : 35A / 250v / 50Hz / p.f. 1

Sizes **5x20mm** : 2 mA to 10 A / 250v

Part Nos. 34-1501 / 1526

**6.3x32mm** : 100mA to 10 A / 250v

Part Nos. 34-1736 / 1756



## SP Quick Acting F High Breaking Capacity


Breaking Capacity : 1500 A / 250v / 50Hz / p.f. 0.7 - 0.8 >6.3A 500A/250v

Sizes **5x20mm** : 500mA to 16 A / 250v

Part Nos. 34-001.1001 / 1016

**6.3x32mm** : 500mA to 20 A / 250v

Part Nos. 34-001.1021 / 1037



## FST Slow Blow (Time Lag) T Low Breaking Capacity

For high inrush or transient loads.


Breaking Capacity : 35A / 250v / 50Hz / p.f. 1

Sizes **5x20mm** : 20 mA to 20 A / 250v

Part Nos. 34-3101 / 3130

**6.3x32mm** : 20mA to 20 A / 250v

Part Nos. 34-3401 / 3430



## SPT Slow Blow (Time Lag) T High Breaking Capacity


Breaking Capacity : 1500A / 250v / 50Hz / p.f. 0.7 - 0.8 >6.3A 500A/250v

Sizes : **5x20mm** : 500mA to 16 A / 250v

Part Nos. 34-001.2501 / 2516

**6.3x32mm** : 500mA to 32 A / 250v

Part Nos. 34-001.2521 / 2539



## SA Super Quick Acting FF High Breaking Capacity

Breaking Capacity is defined as the maximum current the fuse is able to interrupt at its rated voltage. In the event of a fault an inadequate breaking capacity can result in a persistent arc causing serious damage.

Breaking Capacity : 1500A / 250v / 50Hz / p.f. 0.7 - 0.8 (500A 4- to 10A)

Sizes : **5x20mm** : 1.6 A to 10 A / 250v

Part Nos. 34-0903 / 0911

**6.3x32** : 1.6 mA to 16 A / 250v

Part Nos. 34-1001 / 1012




## MSA Axial Lead (Pico) Quick Acting F 125V

Part Number	Rating A
34-4807	.0625
34-4810	.125
34-4813	.250
34-4815	.375
34-4817	.500
34-4820	.750
34-4822	1
34-4824	1.5
34-4826	2

Part Number	Rating A
34-4827	2.5
34-4828	3
34-4831	4
34-4832	5
34-4833	7
34-4834	10
34-4835	12
34-4836	15

UL/CSA

Breaking Capacity : 300A/125v  
>10A 300A/32v



Available loose or taped & reeled 1500pcs

## MSF Microfuse Quick Acting

Pluggable into sub-miniature fuseholder

directly mountable on printed circuit boards.

### MSF 125v

100mA to 5 A

Part Nos. 34-4206/4228

UL, CSA



### MSF 250v

50 mA to 5 A

Part Nos. 34-6000/6021

UL, SEV, VDE-Mark, SEMKO-



## MST 250v Microfuse - Time Lag

Pluggable into sub-miniature fuseholder or directly mountable on printed circuit boards.

Available in sizes 63mA to 4 A / 250v.

Part Nos. 34-6602 / 6623

Breaking Capacity : 35 A or 10. In / 250v AC (p.f. 1) according to IEC 127-3/4

