

Hi-Q Components

Hi-Q Electronics Ltd, PO Box 302 015, North Harbour, Auckland, New Zealand Ph +64 9 415 3333 Fax +64 9 415 8686

Hammond Watertight ABS Boxes

Rugged electronic or electrical watertight enclosure.

Features

- * Light grey ABS material carries a rating of UL94 HB and is not recommended for outdoor use. Refer to Polycarbonate series for outdoor use.
- * Lid is secured with self-captivating M4 stainless machine screws into integral stainless steel bushings to avoid corrosion with dissimilar metals.
- * Gasketed lid with high temp. UL listed silicon gasket material and 2 piece 'tongue & groove' construction to protect against access of oil, dust and water. Meets IP 66 & NEMA 4, 4X, 12 & 13.
- * Vertical card guides moulded in and integral PCB mounts and DIN rail mounting tabs except for smallest sizes BGY & CGY of both series. Options vary with the size. Refer to photo tables on www.hammondmfg.com for internal views of each size, also for detailed drawings and CAD files.



26-1554 Series Flat opaque lid



26-1555 Series Recessed lid for membrane keypad & PCB spacers moulded into lid - designed for #6 self-tapping screws.

Optional gear plate

Part Number - ABS		Length	Width	Height
With flat lid	With recessed lid			
26-1554BGY	26-1555BGY	65	65	40
26-1554EGY	26-1555EGY	90	90	60
26-1554CGY	26-1555CGY	120	65	40
26-1554DGY	26-1555DGY	120	65	60
26-1554FGY	26-1555FGY	120	90	60
26-1554GGY	26-1555GGY	120	90	80
26-1554NGY	26-1555NGY	120	120	60
26-1554PGY	26-1555PGY	120	120	80
26-1554JGY	26-1555JGY	160	90	60
26-1554KGY	26-1555KGY	160	90	90
26-1554RGY	26-1555RGY	160	160	60
26-1554SGY	26-1555SGY	160	160	90
26-1554HGY	26-1555HGY	180	120	60
26-1554TGY	26-1555TGY	180	120	90
26-1554UGY	26-1555UGY	200	120	90
26-1554VGY	26-1555VGY	240	160	90

Hi-Q Components

Hi-Q Electronics Ltd, PO Box 302 015, North Harbour, Auckland, New Zealand Ph +64 9 415 3333 Fax +64 9 415 8686

Hammond Watertight Polycarbonate 'Series 2' Boxes


Rugged electronic or electrical watertight & weather resistant enclosure.

Features

- * Light grey (RAL 7035) polycarbonate material carries a rating of UL94 5V and is recommended for outdoor use.
- * Lid is secured with self capturing M4 stainless machine screws into integral stainless steel bushings to avoid corrosion with dissimilar metals.
- * Gasketed lid with high temperature UL listed silicon gasket material and 2 piece 'tongue & groove' construction to protect against access of oil, dust and water. Meets IP 66 & NEMA 4, 4X, 12 & 13.
- * Vertical card guides, integral PCB mounts and DIN rail mounting tabs moulded in except for the smallest sizes BGY & CGY of both series.
- * Clear flat polycarb. lid version (1554 '2' series) for use with sensors and photovoltaics.
- * Options vary with size. Refer to photo tables on www.hammondmg.com for internal views of each size, also for detailed drawings and CAD files.



26-1554 '2' Series Flat opaque lid and clear lid option



Optional gear plate

26-1555 '2' Series Recessed lid for membrane keypad & PCB spacers in lid.

Part Number - Polycarbonate			Length	Width	Height
With flat lid	With clear lid	With recessed lid			
26-1554B2GY	26-1554B2GYCL	26-1555B2GY	65	65	40
26-1554E2GY	26-1554E2GYCL	26-1555E2GY	90	90	60
26-1554C2GY	26-1554C2GYCL	26-1555C2GY	120	65	40
26-1554D2GY	26-1554D2GYCL	26-1555D2GY	120	65	60
26-1554F2GY	26-1554F2GYCL	26-1555F2GY	120	90	60
26-1554G2GY	26-1554G2GYCL	26-1555G2GY	120	90	80
26-1554N2GY	26-1554N2GYCL	26-1555N2GY	120	120	60
26-1554P2GY	26-1554P2GYCL	26-1555P2GY	120	120	80
26-1554J2GY	26-1554J2GYCL	26-1555J2GY	160	90	60
26-1554K2GY	26-1554K2GYCL	26-1555K2GY	160	90	90
26-1554R2GY	26-1554R2GYCL	26-1555R2GY	160	160	60
26-1554S2GY	26-1554S2GYCL	26-1555S2GY	160	160	90
26-1554H2GY	26-1554H2GYCL	26-1555H2GY	180	120	60
26-1554T2GY	26-1554T2GYCL	26-1555T2GY	180	120	90
26-1554U2GY	26-1554U2GYCL	26-1555U2GY	200	120	90
26-1554V2GY	26-1554V2GYCL	26-1555V2GY	240	160	90