


Black Polyamide Plastic Base 40 Dia. - 30 Deg. Articulated Stainless Steel Screw


Static Load 10000 Newton • Non-Skid NBR Rubber 70 shore pads available

Part no. Base	Screw	A	B	D	Adjust	F	G	H
11-AFP40SS8-50	M8X50	27	50	40	12	M8	16.5	77
11-AFP40SS8-75	M8X75	27	75	40	12	M8	16.5	102
11-AFP40SS10-25	M10X25	27	25	40	12	M10	16.5	52
11-AFP40SS10-50	M10X50	27	50	40	12	M10	16.5	77
11-AFP40SS10-75	M10X75	27	75	40	12	M10	16.5	102

**Plastic Base 50mm Dia. with Articulated Stainless Steel Screw 30 deg.**


Black Polyamide

Part no.	Screw	A	B	D	F	G	H	Newton
11-AFP50SS10-75	M10x75	30	75	50	M10	20	105	11000
11-AFP50SS12-50	M12x50	30	50	50	M12	20	80	11000

**Flat Plastic Base 83mm Dia. with Articulated Steel Screw 30deg**

Black Polyamide


Part no.	Screw	A	B	D	F	G	H	Newton
11-AFP83S10-50	M10X50	30	50	83	M10	18	83	10000
11-AFP83S12-100	M12X100	30	100	83	M12	18	130	13000
11-AFP83S12-50	M12X50	30	50	83	M12	18	80	13000
11-AFP83S16-100	M16X100	30	100	83	M16	18	130	16000



Black Polyamide Plastic Base 40 Dia. - 30 Deg. Articulated Stainless Steel Screw


Static Load 10000 Newton • Non-Skid NBR Rubber 70 shore pads available

Part no. Base	Screw	A	B	D	Adjust	F	G	H
11-AFP40SS8-50	M8X50	27	50	40	12	M8	16.5	77
11-AFP40SS8-75	M8X75	27	75	40	12	M8	16.5	102
11-AFP40SS10-25	M10X25	27	25	40	12	M10	16.5	52
11-AFP40SS10-50	M10X50	27	50	40	12	M10	16.5	77
11-AFP40SS10-75	M10X75	27	75	40	12	M10	16.5	102

**Plastic Base 50mm Dia. with Articulated Stainless Steel Screw 30 deg.**


Black Polyamide

Part no.	Screw	A	B	D	F	G	H	Newton
11-AFP50SS10-75	M10x75	30	75	50	M10	20	105	11000
11-AFP50SS12-50	M12x50	30	50	50	M12	20	80	11000

**Flat Plastic Base 83mm Dia. with Articulated Steel Screw 30deg**

Black Polyamide

Part no.	Screw	A	B	D	F	G	H	Newton
11-AFP83S10-50	M10X50	30	50	83	M10	18	83	10000
11-AFP83S12-100	M12X100	30	100	83	M12	18	130	13000
11-AFP83S12-50	M12X50	30	50	83	M12	18	80	13000
11-AFP83S16-100	M16X100	30	100	83	M16	18	130	16000



ADJUSTABLE LEVELLING FEET

HOW TO ORDER

STEP 01

SCREW MATERIAL

ZINC PLATED STEEL
STAINLESS STEEL



STEP 02

SCREW SOCKET SIZE

12 SOCKET - SUITED TO M8 - M12
15 SOCKET - SUITED TO M10- M20



STEP 03

THREAD SIZE & LENGTH

THREAD SIZES RANGE FROM
M8 - M20.

AVAILABLE THREAD LENGTHS:
25 - 225MM



STEP 04

PLASTIC BASES

MATCH YOUR BASE SOCKET SIZE
TO THE SAME SOCKET SIZE AS
YOUR SCREW.

12 SOCKET - SUITED TO M8 - M12
15 SOCKET - SUITED TO M10- M20



CHOOSE YOUR BASE DIAMETER.
40MM TO 123MM AVAILABLE.

HOT TIP: IT IS VERY IMPORTANT THAT THE SOCKET SIZE YOU CHOOSE FOR
YOUR SCREW (12 OR 15), MATCHES THE SOCKET SIZE OF YOUR BASE.

NEED MORE GRIP ON YOUR LEVELLING FEET?

OPTIONAL NON SKID RUBBER PAD AVAILABLE. MATCH THE DIAMETER OF YOUR BASE TO THE PAD YOU NEED.



PART NUMBER BREAKDOWN

SCREW PART NUMBER

ASS = ZINC PLATED STEEL
ASSS = STAINLESS STEEL
(EXAMPLE = ZINC PLATED SCREW)

050 = 50MM
THREAD LENGTH

↑
11-ASS15-10-050

↓
15 = SOCKET SIZE

↓
10 = M10 THREAD

STEP 05

BASE PART NUMBER

50 = DIAMETER SIZE

↑
11-FPB15-50

↓
15 = SOCKET SIZE

Hi-Q
components