



Hammond Diecast Aluminium - 1550 - Light Duty Watertight 1550W Rugged, diecast aluminium alloy. Tough yet easy to machine.

- Lap joint construction protection against access of dust and splashing water
 Designed to meet IP54. Watertight version 1550W designed to meet IP66.
 1550W Lap joint construction with a self-adhesive, EVA foam gasket provides protection against access of dust & water.
 Painted version is painted outside with touch polyester powder paint for lasting finish.(RAL7001)
- Assembled with stainless steel machine screws.
- No internal ribs for easy installation of connectors without interference or additional milling.
- Low side wall draft angle (2 degrees or less) for easy P.C.B mounting.





1550 Series



1550W Series

For detailed drawings and CAD files visit ww.hammondmfg.com

Part Number						
1550 Series		1550W Series		Length	Width	Height (No Lid)
Unpainted	Black	Unpainted	Black			
26-1550Q	26-1550QBK	26-1550WQ	26-1550WQBK	60	55	26
26-1550P	26-1550PBK	26-1550WP	26-1550WPBK	80	55	21
26-1550A	26-1550ABK	26-1550WA	26-1550WABK	89	35	26
26-1550B	26-1550BBK	26-1550WB	26-1550WBBK	115	64	26
26-1550D	26-1550DBK	26-1550WD	26-1550WDBK	115	64	51
26-1550C	26-1550CBK	26-1550WC	26-1550WCBK	115	90	51