

Standard Strap Type – PCV Series UV Resistant - Black

Manufactured from tough, durable Nylon 6/6 with carbon added for UV resistance

Part Number	Length L mm	Width W mm	Bundle Max. Diameter	Min. Tensile Strength Kg
15-PCV060/2.4W	60	2.4	11	8
15-PCV075/1.6W	75	1.6	11	8
15-PCV200/2.5W	200	2.5	55	8
15-PCV200/4.6W	200	4.6	52	22
15-PCV200/4.8W	200	4.8	52	22
15-PCV200/7.6W	200	7.6	52	55
15-PCV250/4.8W	250	4.8	68	22
15-PCV300/4.8W	300	4.8	83	22
15-PCV340/7.6W	340	7.6	92	55
15-PCV370/4.8W	370	4.8	94	34
15-PCV380/8.0W	380	8.0	105	60
15-PCV432/4.8W	432	4.8	125	22
15-PCV450/8.0W	450	8.0	128	60
15-PCV500/4.8W	500	4.8	128	60
15-PCV610/4.8W	610	4.8	181	22
15-PCV635/4.8W	635	4.8	181	22
15-PCV914/9.0W	914	9.0	275	80
15-PCV1500/9.0W	1500	9.0	462	80

Standard Strap Type NT Series

Manufactured from tough, durable Nylon 6/6 with a flammability rating of UL 94V2

Tensile strength meets MIL-S-23190D (PCV type) MIL-S-23190E (NT type)

Part Number	Length L mm	Width W mm	Bundle Max. Diameter	Min. Tensile Strength Kg
15-NT08025	80	2.4	16	8.1
15-NT08025B	80	2.5	16	8.1
15-NT10025	100	2.5	20	8.1
15-NT10025B	100	2.5	20	8.1
15-NT14036	140	3.2	32	18.0
15-NT14036B	140	3.2	32	18.0
15-NT16025	160	2.5	38	8.1
15-NT16025B	160	2.5	38	8.1
15-NT20025	200	2.5	50	8.1
15-NT20025B	200	2.5	50	8.1
15-NT20036	200	3.6	50	18.0
15-NT20036B	200	3.6	50	18.0
15-NT25048	250	4.8	68	22.0
15-NT25048B	250	4.8	68	22.0
15-NT29076	280	7.6	78	55.0
15-NT29536	295	3.6	82	18.0
15-NT29076B	280	7.6	78	55.0
15-NT29536B	295	3.6	82	18.0
15-NT29548	295	4.8	82	22.0
15-NT29548B	295	4.8	82	22.0
15-NT37048	370	4.8	107	22.0
15-NT37048B	370	4.8	107	22.0
15-NT43248CB	432	4.8	125	22.0
15-NT45090	450	8.0	133	80.0
15-NT45090B	450	8.0	133	80.0
15-NT61090B	610	9.0	185	80.0

Std Stock in Natural Nylon 6/6.

Suffix B Denotes Black UV Resistant NT Series

