

## Cable Entry Caps / Desk Grommets

Features a smooth design for desktop mounting

| Part Number | Outside Diameter | Colour |
|-------------|------------------|--------|
| 14-DGB60    | 60mm             | Black  |
| 14-DGG60    | 60mm             | Grey   |
| 14-DGW60    | 60mm             | White  |

Other colours available to order.



## Insulating Bushes - Miniature


Insulate wires and cables from raw edges • Snaps quickly into panel hole • Accomodate panels up to 1.6mm thick

Requires internal clearance of only 3.2mm.


Temperature Index 105°C.

| Part Number | Panel Hole Diameter | Max. Cable Diameter A | Overall Length C | Outside Diameter B |
|-------------|---------------------|-----------------------|------------------|--------------------|
| 22-PPB05    | 4.8                 | 3.2                   | 6.2              | 6.4                |
| 22-PPB08    | 8.0                 | 6.4                   | 6.2              | 9.5                |
| 22-PPB12    | 11.9                | 8.8                   | 6.4              | 13.5               |
| 22-PPB13    | 12.7                | 9.5                   | 6.4              | 14.3               |
| 22-PPB14    | 13.5                | 10.3                  | 6.4              | 15.2               |
| 22-PPB16    | 15.9                | 12.7                  | 6.4              | 17.9               |
| 22-PPB19    | 19.0                | 16.0                  | 6.4              | 21.0               |
| 22-PPB22    | 22.2                | 19.0                  | 6.4              | 23.8               |

Material: Black Heat Stabilized Nylon 6/6 UL94V2



MINIATURE BUSHING




## Insulating Bushes - Standard

Standard bushes have multiple locks which snap positively into panels ranging from 0.8 to 3.2 mm thick

Meets UL & CSA Temperature and Pull-out tests.

Temperature Index 105°C.

| Part Number | Panel Hole Diameter | Max. Cable Diameter A | Overall Length C | Outside Diameter B | Max. Panel Thickness |
|-------------|---------------------|-----------------------|------------------|--------------------|----------------------|
| 22-PLB06    | 6.3                 | 3.2                   | 8.0              | 8.0                | 1.6                  |
| 22-PLB08    | 8.0                 | 4.8                   | 8.0              | 9.5                | 1.6                  |
| 22-PLB09*   | 9.5                 | 6.3                   | 10.3             | 11.9               | 3.2                  |
| 22-PLB09X   | 9.5                 | 4.8                   | 10.3             | 11.9               | 3.2                  |
| 22-PLB11    | 11.1                | 8.0                   | 10.3             | 13.5               | 3.2                  |
| 22-PLB13X   | 12.7                | 9.5                   | 10.3             | 14.7               | 3.2                  |
| 22-PLB14X   | 14.3                | 11.4                  | 10.3             | 17                 | 3.2                  |
| 22-PLB16X   | 15.9                | 12.7                  | 10.3             | 18.6               | 3.2                  |
| 22-PLB19X   | 19.1                | 14.8                  | 10.3             | 21.4               | 3.2                  |
| 22-PLB22    | 22.2                | 17.4                  | 11.5             | 24.2               | 3.2                  |
| 22-PLB22X   | 22.2                | 17.5                  | 11.5             | 24.2               | 3.2                  |
| 22-PLB25X*  | 25.4                | 19.5                  | 11.7             | 28.5               | 3.5                  |
| 22-PLB28*   | 27.8                | 23.8                  | 11.5             | 30.9               | 3.2                  |
| 22-PLB30X   | 30.1                | 24.1                  | 11.5             | 33.3               | 3.2                  |
| 22-PLB32X   | 31.7                | 23.8                  | 11.4             | 34.6               | 3.5                  |
| 22-PLB35    | 34.9                | 25.4                  | 11.5             | 37.3               | 3.2                  |
| 22-PLB38X   | 38.1                | 29                    | 11.4             | 42.1               | 3.2                  |
| 22-PLB44    | 44.4                | 34.9                  | 11.5             | 47.6               | 3.2                  |
| 22-PLB50X*  | 50.8                | 41.6                  | 11.8             | 54.6               | 3.2                  |
| 22-PLB57    | 57.1                | 44.5                  | 18.3             | 63.0               | 6.4                  |
| 22-PLB63    | 63.5                | 49.9                  | 18.4             | 68.5               | 6.4                  |
| 22-PLB76    | 76.2                | 62.7                  | 18.3             | 80.2               | 6.4                  |
| 22-PLB85    | 85.7                | 71.4                  | 18.3             | 92.9               | 6.4                  |
| 22-PLB89    | 88.9                | 74.6                  | 18.3             | 92.9               | 6.4                  |
| 22-PLB101   | 101.6               | 87.8                  | 18.3             | 105.9              | 6.4                  |



Material: Black Heat Stabilized Nylon 6/6 UL94V2

\* = Available in white.